

Hyosung's proven, reliable, full-function ATM.

Designed to provide unprecedented reliability, the **7T** is unparalleled in the market. This full-function through-the-wall ATM can easily be upgraded from a cash dispenser to deposit automation and supports large volume transactions. The **7T's** highest uptime and minimum maintenance has helped make Hyosung the fastest growing ATM company.

Features

High Availability

The innovative design and the use of Hyosung manufactured core technologies allows for fast, easy replenishment and reduced down time. The **7T** is designed to provide reliability that is unequalled in the market, with minimum maintenance and maximum uptime.

Flexibility

The **Series 7 ATMs** can also be easily upgraded from a cash dispenser to deposit automation should an institution decide to implement the technology later.

Capacity

High capacity, cash dispense capability and the ability to support large volume transactions.



Specifications

Dimensions

- Height: 54.4 inch (1383 mm)
- Width: 28.4 inch (721 mm)
- Depth: Safe: 32.1 inch (815 mm)
with Collar: 11.3 inch (288 mm)
- Weight: 1,576.3 lbs (715 kg)

Environmental Conditions

- Temperature: 32°F – 104°F (0°C ~ 40°C)
With Heater: 14°F - 104°F (-10°C ~ 40°C)
- Humidity 25% – 85%

System Platform

- Microsoft Windows® 10
- Hyosung MoniPlus™ including Hyosung MoniGuard™ Security
- Hyosung MoniCRM™
- Hyosung Connect
- Hyosung MoniManager™

Customer Interface

- 15" LCD touch screen
- Privacy filter
- PCI complaint EPP
- Headphone jack with Volume Control
- Card Reader – DIP reader, EMV compliant
- Contactless – Integrated reader (via card, smartphone, or smartwatch)

Media Handling

- **Cash Dispenser**
 - Configurable denominations up to 4 high capacity dispense cassettes
 - 3,000 notes* per cassette
 - Bundle present, bundle retract
 - Note by note rejection
 - Automatic shutter
- **Cash & Check InModule (CCIM)**
 - Maximum capacity Mixed 50 cash/checks per bundle per transaction
 - Up to 2,000 notes* cassette capacity
 - Up to 2,000 checks* cassette capacity
 - Reject and retract capability

Security

- UL291 Level 1 Safe
- Seismic & Heat detector
- Locking Device – Electronic, mechanical combination lock, Kaba Mas Cencon lock (optional)
- IP or Analog security camera (optional)
- Awareness Mirror
- Hyosung MoniGuard™ Solutions
- Trusted Platform Module (TPM)

Printer

- 3.1" graphical thermal receipt printer

Servicing

- Rear access
- State of health indicators for all modules

Power Supply

- AC 100V ~ 127V±10%,
200V ~ 240V±10% 50/60Hz

Additional Features

- Backup battery reserves the last transaction & safe shutdown
- Heater support operating
- Barcode reader (optional)

*Subject to media quality and other variables

Note: Internal components may change with the introduction of new technology. Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.